

## Satellite Speakers

USA product, Dolby Digital compatible designed to complement the latest flat-panel and plasma televisions perfectly, the speaker can be placed virtually anywhere



Designed to complement the latest flat-panel and plasma televisions perfectly, the Infinity 3-way Satellite Speaker can be placed virtually anywhere. Each satellite includes three different height shelf stands, so matching the speaker to the television's height is easy.

The infinity speaker features MMD™ drivers for maximum sound response. Place the satellite speaker on a shelf or mount it on a wall using the included bracket, which allows you to aim the sound at your listening area. An optional floor stand and in-wall recess kit are also available. The solid, extruded-aluminum enclosure is highly rigid to reduce unwanted resonance even at high listening levels.

The Infinity speaker is Dolby Digital or DTS receiver compatible. Four woofers at the top and bottom surround a pair of midrange drivers and an MMD-dome tweeter in the center. These drivers use Infinity's proprietary MMD cones throughout and are arrayed in a three-way design to maximize both frequency response and power handling. The MMD cone conducts sound faster than paper, polypropylene and Kevlar®, pushing unwanted resonance beyond the operating range of the transducer. In addition, this speaker is magnetically shielded for safe placement adjacent to a television.

- Applications:**
- Audio for Luxury Homes
  - Audio at Luxury Offices
  - Hotel Banquet Halls Audio
  - Smart School Audio Sharing in Auditoriums
  - Home Theater Cinema Experience

**Model:** SH-530

**Part #:** Infinity 3way satellite speaker

### Features

- Three height shelf stands provided to match television height
- Speaker features four woofers, two midrange drivers and an MMD-dome tweeter
- Magnetically shielded for safe placement near television

### Specifications

Frequency Response: .....  
 120Hz - 20kHz (±3dB)  
 Nominal Impedance: 8 ohms  
 Sensitivity (2.83V @ 1m): 89dB  
 Recommended Amplifier Power Range:  
 10 - 150 watts  
 Crossover Frequencies: .....  
 1,000Hz, 3,800Hz; 24dB/octave  
 Low-Frequency Drivers:.....  
 (4) 3-1/2" (89mm), MMD, magnetically shielded  
 Mid-Frequency Drivers:.....  
 (2) 3-1/2" (89mm), MMD, magnetically shielded  
 High-Frequency Driver:.....  
 3/4" (19mm), MMD, elliptical waveguide, magnetically shielded

### Dimensions

Size: .....  
 23" x 4 1/8" x 4 3/8"  
 584mm x 105mm x 111mm

Weight: 12.7 lbs. (5.8kg)