## **Indoor High Speed Dome Camera**



- Applications: Camera Security for Luxury Homes
  - **CCTV Security at Luxury Offices**
  - Hotel Security and Surveillance
  - Smart School Supervision and Observation

Model: SH-560

Part #: D-Max DCS230Si

## **Features**

- 1/4 " SONY Super HAD CCD
- 6.6-inch Bubble((Poly-
- Carbonate)Vandal proof))
- 360° Continuous, 92° Vertical
- Pan Speed:360°/sec, Tilt Speed:200°/sec
- Auto Flip(180°)
- Alarm: 4CH Active high/low selective input, 1 Relay output

## **Specifications**

Signal System: PAL Number of total pixels: ..... 795(H)X596(V), 470K Number of effective pixels: .... 752(H)X582(V), 440K Horizontal resolution: ..... More than 480 TV Lines Lens:22x Optical zoom, F 1.5(Wide) -3.8(Tele), f =3.9-85.8mm, Video AF Digital zoom:.. 10x (Total zoom 220x) Image sensor:.... 1/4 " SONY Super HAD Minimum Shooting Distance: .... 0.01m(Wide), 1.0m(Tele) Luminance S/N ratio: More than 48dB(AGC Off) OSD: On/Off Video output: 1 Vp-p Composite video output 75 ohm terminated Sync System:..... Internal / External (Line Lock) Focus mode: ..... Auto/manual/Oneshot Brightness control:..... Level control (Up/Down) White balance: Auto / Push Auto Power consumption: 18W (Max)
Operating Humidity: ...... Less than 90%RH Storage temperature: -  $5^{\circ}$  C to  $60^{\circ}$ Operating temperature: ..... - 15° C to 60° Communication System:..... RS-485/422 Preset Speed:. 0.1°-360°/sec (64 steps) Tilt speed: Manual:0.1°-90°/sec (64 levels), Preset: Tilt rotation angle: -2° ~ 90° Max speed control: ..... Lower / Middle / High

## **Dimensions**

Size:189D x 224H (mm) Weight: About 3.2Kg

