

Surveillance Keyboard Control

Multi-Speed control, Fully Functional, Variable speed, PTZ Surveillance Control Keyboards.



Accessories



Junction Box



Connection Cable



Adaptor



Manual



Control Keyboard

Max distance up to 500m
RJ45 898C Cables

RS148 TO RS232



D-SUB9 Cables



JPEG2000 DVR

- Applications:**
- Camera Security for Luxury Homes
 - CCTV Security at Luxury Offices
 - Hotel Security and Surveillance
 - Smart School Supervision and Observation

Model: SH-577

Part #: D-MAX DCK255 Keyboard

Specifications

Control:.....
 Pan/Tilt, Zoom, Power, Auto Pan, AUX Control x 2, Preset
 Connecting Unit: CCTV Receiver (DRX-502/500), PTZ Dome Cameras
 Communication Method:
 RS-485 (422)
 Communication Speed:
 RS485 - 9600bps, N, 8, 1
 Connector:
 Modular cable connection with junction box; Power supplied via junction box
 Package:
 Junction Box, 5M cable (modular jacks both ends)
 Operating Distance:
 Max. 1.2km (When using shielded twisted pair cable)
 Power: DC9V, 500mA
 Power Consumption: 6W
 Operating Condition: 0°C ~ +40°C

Dimensions

Size: 337.5Wx83.8H x179.2D (mm)
 Weight: 1.0kg, Junction Box 220g

Model: SH-578

Part #: Ntic JPEG2000 Series

Features

- Transmission setting in 19200 band rate. 1 start bit, 1 stop bit and no parity.
- Max distance up to 500m.

Specifications

Power: DV12V/1A adaptor
 Power Consumption: 0.7W
 Operating temp: 1°C ~ 50°C

Dimensions

Size: 340x140x44mm
 Weight: 1.0kg, Junction Box 220g