

Emergency Dialers

In case of emergency situation, it provides convenient hands free communication



The E-10 Emergency Dialer are designed to provide two-way hands free communication. The E-10 can be connected directly to a C.O. line or analog PABX/KSU station when used in conjunction with a Hot-Line Dialer or programmed ring down circuit. It can also be used with Viking's DLE-200B ring down circuit.

When the "Call" button is pressed, the E-10 will come off-hook and will remain off-hook until CPC is detected or the pre-selected timeout has elapsed (adjustable from approximately 6 seconds - 5 minutes). During this time the user may converse handsfree.

For outdoor or harsh environments, the E-10 is available with EWP (Enhanced Weather Protection). EWP products feature rubber gaskets and boots, hand soldered silicon sealed connections, gel filled tip and ring connectors, as well as urethane potted circuit boards with weather sealed, field-adjustable trim pots and DIP switches for easy on-site programming.

- Applications:**
- Commercial, industrial and residential door security
 - Truck stop/gas station fuel island communication
 - Business delivery entrances
 - Tower Elevators

Model: SH-606

Part #: Viking E10

Features

- Telephone line powered
- Call timer on/off switch
- Adjustable time out to limit prank calls and false alarms (approximately 6 seconds - 5 minutes)
- Auto-answer feature allows remote monitoring (can be disabled)
- Weather resistant
- Optional EWP (Enhanced Weather Protection)
- Adjustable microphone and speaker volume
- One year warranty
- Vandal resistant, black powder painted, aluminum face plate with mounting gaskets
Flush mountable using included rough-in box

Specifications

Power: Telephone line powered (18 VDC/20mA minimum)
 E-10 Dimensions: Overall: 127mm x 127mm x 57.2mm (5" x 5" x 2.25"),
 Rough-in box: 102mm x 102mm x 57mm (4" x 4" x 2.25")
 E-20A Dimensions: 140mm x 115mm x 38mm (5.5" x 4.5" x 1.5")
 Shipping Weights: E-10: 0.91 kg (2 lbs),
 E-20A: .75 kg (1.5 lbs)
 Standard E-10/E-20A Environment: -26° C to 54° C (-15° F to 130° F) with 5% to 95% non-condensing humidity
 E-10/E-20A-EWP Environment: -26° C to 54° C (-15° F to 130° F) with up to 100% condensing humidity
 Speaker Volume: Approximately 70db maximum @ 1m
 Ring Voltage: 30V AC RMS minimum
 CPC Disconnect
 Time: 300ms minimum REN: 0.7A
 Standard Connections: (1) 2-position terminal block
 EWP Connections: (2) gel-filled butt connectors