





AM-001 AAA+ Home Smart Control Panel

Product Sheet

4 in One Home Smart Control Panel

Alarm • Alert • Automation • Communicator



Alarm

- Arm, Away mode.
- 45s exit delay and 30s entry delay
- Master and secondary PIN
- 5 zones, up to 10 sensors
- Delay alarm, Instant alarm, Bypass
- Incorrect PIN alarm
- Tamper switch
- Duress PIN
- Panic Activation
- Built-in Siren

Automation

- Turn on/off up to 5 electrical devices by wireless control modules
- Remotely control appliances by calling in from any touch tone telephone
- Event Trigger Automation.

Alert

- Audio and Visual warning to indicate locations of triggered zones and sensors.
- Voice cues that support announcements for sensor's status
- Auto and manual mute
- Remote event notification by calling in

Auto Dialer

- Build-in auto dialer.
- 5 programmable telephone numbers for voice message
- 1 programmable telephone numbers for monitoring center
- Supports Contact ID (General Alarm)
- Fault line monitoring
- Support tone / pulse dialing

Communicator

- User can call in to check system status, to arm or disarm security function, or to turn on/off power devices.
- Calls up to 5 phone numbers during emergency.

Voice Cue

- System announcement by human voice.
- Available in operations and programming.
- Available when remote control by phone.
- Languages available: English, French, Spanish and German.

Accessories (Optional)

- Indoor/Outdoor Motion Sensor
- Door/Window Sensor
- Garage Door Monitor™ Sensor
- Audio Sensor
- Water Sensor
- Remote Control
- Keypad Control
- Panic Transmitter
- Control Module (Signal Acknowledgement)
- Audio Alarm
- Repeater

System Features

- 5 programmable and supervised zones
- Compatible with 10 sensors (max)
- Compatible with 5 control modules (max)
- Compatible with 5 keychain remotes (max)
- System failure indication
- Low battery indication
- System alert by Beeping, LED and voice cue

Radio Frequency

- Skylink® Rolling Code
- Frequency 433.92 MHz
- Operating range 60m (200 feet)

Working Environment

- Operating temperature 0° - 60°C

Power Supply

- 12VDC by AC adapter (included)
- Back up by 4 x AAA alkaline batteries (included)
- Backup batteries provides 48 hours of standby operation

Dimensions

- 160 x 110 x 55 mm
- Weight 213g
- ABS plastic housing

Mounting

- Desktop

International Approval

- FCC, ETL, CE