# Sensaphone® 1104 Desktop Monitoring System

**Environmental/Process monitoring** 

over telephone lines with full programming capabilities

- ☐ The versatile Model 1104 is designed for programming flexibility
- ☐ Variable alarm recognition and "listen-in" time, with alarm disable, security code access, remote sensing, and other programming features
- ☐ Monitors power, temperature, and other important environmental conditions to protect computers, equipment, and processes
- Automatically contacts you at up to 4 locations if unsafe conditions occur
- Allows you to contact your system using any telephone, to receive status reports and listen-in to on-site sounds
- ☐ Helps you detect problems before they turn into disasters

Now you can protect your equipment and processes even when you can't be there - The Sensaphone 1104 monitors your computer rooms, equipment centers, offices, or any unattended facility to detect power failures, temperature extremes, intrusions, water incursion, sounds such as smoke and burglar alarms, and other conditions of your choice.

Alerts you immediately if problems arise - The Sensaphone 1104 automatically contacts you by phone at up to four different phone numbers, to alert you of unsafe conditions. The system communicates in voice-synthesized English, and even lets you "listenin" to actual on-site sounds.



CONDITIONS MONITORED:

Temperature
Humidity
Electricity
Water Incursion
Smoke
Sound
Windows &
Doors

...and more!

ALLINI

**UP TO 4 DIAL-OUT NUMBERS** 

If unsafe conditions occur, the Sensaphone will automatically dial up to four numbers in sequence to advise you of the problem. Numbers may be up to 32 digits each, with your choice of pulse or tone dial-out.



COMMUNICATES OVER STANDARD PHONE LINES:

Call-in for periodic status reports on all monitored conditions, using any telephone. The Sensaphone communicates in simple voice-synthesized English.

Phonetics, Inc.

See reverse side for a list of the Sensaphone's outstanding features and capabilities.

# Sensaphone® 1104



**Ideal for a variety of applications** - The Sensaphone is useful wherever there is a need for monitoring of temperature, humidity, or other conditions. Sensors and input devices are available to suit a wide range of applications.

|      | 8 11  |
|------|---|
|      | HVAC Equipment Computer rooms Refrigeration and freezers Health care centers Offices Warehouses Livestock and egg/poultry Home & property Greenhousesand many others! |
| BUII | T-IN FEATURES   |
|      | 4 User-selectable inputs, temperature or dry-contact  |
|      | Microphone monitors high sound alarms and enables remote listen-in  |
|      | AC Power failure sensing with variable recognition time   |
|      | Battery condition monitor<br>Clock  |
| ADV  | ANCED CAPABILITIES  |
|      | User Programmable: Alarm recognition time, Call delay, Inter-call delay, Message repetitions  |
|      | Temperature sensing in Fahrenheit (-20°F to 150°F), or Celsius (-29°C to 65°C)  |

## VERSATILE DIAL-OUT CAPABILITIES

|   | Alert sensors trigger pulse or tone    |
|---|--|
|   | dialout automatically                  |
|   | Dials up to 4 numbers, up to 32 digits |
|   | each                                   |
|   | Continues dialing numbers in sequence  |
| _ | until acknowledged                     |
|   | Call Progress: Intelligently detects   |
| _ | ringing or busy signal                 |
|   | Intelligent dial out to beepers and    |
| _ | pagers                                 |
|   |  |

#### **EASY CONTROL ACCESS:**

| LADI | CONTROL ACCESS.                           |
|------|---|
|      | Keypad for local programming and          |
|      | status report                             |
|      | Unit can be called from any phone to      |
|      | verify status of all monitored conditions |
|      | Local or remote enabling/disabling of     |
|      | all dial-out conditions                   |
|      | Can share a single phone line with an     |
|      | answering machine, allowing full          |
|      | operation of both units                   |
| П    | Programmable security code access         |

### **SPECIFICATIONS**

**Size:** 7<sup>1</sup>/<sub>2</sub>" W, 2" H, 8<sup>1</sup>/<sub>2</sub>" D

**Batteries:** (6) 1.5 Volt "D" cell alkaline (not included) **Telephone Interface:** FCC approved RJ-11 plug-in

modular connector with 6' cord

**Operating Range:** Unit should be kept between 32° F

and 120° F.

**Temperature Sensing Range:** -20° F to 150° F with

remote temperature sensor. **Shipping Weight:** 4 lbs

NRTL listed for compliance with U.L. Standard 1459.

Technical data subject to change without notice.

We'd like to show you how the Sensaphone 1104 can help you monitor your equipment and facilities. Give us a call to find out more! Or listen to an actual Sensaphone report by calling 610-558-4591.



Individual temperature input calibration

Nonvolatile memory for all programmed

parameters

