

## Multi-Room Matrix A/V Controller 6-36 Zones

USA Product with Reputation known since 1967, has pioneer in the multi room audio industry, that is why it is recognized as a preferred source for audio distribution equipment world wide.



### Awards



The award-winning sophisticated CAV6.6 multizone controller is a star performer. It operates behind the scenes distributing six audio/video sources to six entertainment areas within your home. Think of it as audio and video convenience. Or, think of it as having a home entertainment system in every room you want. And if your needs grow, there are built-in A-BUS ports for sub-zones, a feature offering expandability that lets you easily add more entertainment areas.

Simply push the button and see what awaits you. Beautiful music or video that brightens your days and calms your nights, anywhere in your home. That's the UNO experience. Small in size, yet big in performance, an UNO-S2 Smart Keypad is the size of a double-gang switchplate.

Discreetly flush mounted, in your choice of five colors, the keypad blends with nearly every décor and lifestyle. Virtually foolproof, an UNO keypad turns your universe into a joyful one. It simplifies your home entertainment possibilities by giving you more control over your source components. And, it adds value to your Smarthome lifestyle.

- Applications:**
- Audio Video Distribution for Luxury Homes
  - Audio Video Distribution at Luxury Offices
  - Hotel Banquet Halls A/V System Distribution & Control
  - Smart School Media Sharing and Distribution

**Model:** SH-513

**Part #:** Russound CAV6.6 AV Controller

### Features

- Favorite program presets
- System on and off from any keypad Infrared remote control
- Party mode
- Program information from RNET® sources displayed on the keypads
- Paging and doorbell muting capability
- Enjoy a galaxy of music and movies from any seat in the house.

### Specifications

Power supply: 115 or 230 VAC  
 Fuse rating: 120V input; 3A F.B. 250V US and Canada  
 240V input: F1.25A L 250V Europe  
 Frequency response:.....  
 20 Hz-20 kHz +/- 0.5 dB  
 Watts per channel:.....  
 20 watts RMS x 12 into 8 Ohms  
 Total harmonic distortion: 0.05%  
 Signal to noise ratio: 88 dB  
 A/V source inputs:.....  
 7 (including front AUX A/V input)  
 A/V source outputs:  
 6 Zones 6 (expandable up to 6 controllers or 36 zones)  
 A-BUS ready ports: 4  
 Source audio input:.....  
 5V peak to peak, 10k Ohms  
 Source audio loop output:.....  
 Unity gain, 10k Ohms  
 Source video input:.....  
 4.5V peak to peak, 75 Ohms  
 Source video loop output:.....  
 4.5V peak to peak, 75 Ohms  
 Zone video output:.....  
 4.5V peak to peak, 75 Ohms  
 Trigger outputs:.....  
 6 zone, 1 common, 12VDC 50mA each  
 Trigger inputs: 1 home theater

### Dimensions

Size: 17"W x 12"D x 3.5"H  
 43 x 30.5 x 9 (cm)