

## Satellite Receivers

Spain Product known since 1958, is constantly striving to increase its level of service to customers, through quality control, competitive prices and after-sales service



This receiver has a state-of-the-art features, its video decoder can decode mpeg-2 with a process rate of greater than 15Mbits/s and its stunning audio decoder can process MPEG-1 layer both I & II version.

This Hi-end product has its at most preferred system. It is equipped with STi5500 processor , RAM is 2 Mbytes and Flash Memory 1Mbyte with a good graphics rate of 720x576 on PAL and 720x480 NTSC. This device is cost effective and hi standard.

- Applications:**
- Satellite Distribution Control for Luxury Homes
  - Satellite Distribution Control in Luxury Offices
  - Hotel Satellite Distribution Control
  - Smart School Satellite Distribution Control Sharing

**Model:** SH-539

**Part #:** Televes RSD 7235

### Specification

Video Decoder:  
 MPEG-2 Main Profile  
 Process rate >15Mbits/s  
 Video Format 4:3,16:9  
 Audio Decoder:  
 MPEG-1 Layer 1&2  
 Mono,Dual,Stereo,Join  
 Stereo  
 System:  
 RAM 2Mbyte  
 FMem 1Mbyte  
 Graphics 720x576(PAL)  
 720x480(NTSC)  
 LNB input / tuner:  
 Connector 2x"F"  
 Input Freq.: 950x2150MHz  
 LNB powering: 13/18v. max  
 Band Switching: 22KHz tone  
 TV Scart: RGB,CVBS,Audio  
 VCR Scart: CVBS(inpt/outpt)  
 Hi-Fi Output: 2xRCA(I/R)  
 Serial Data Interface: .....  
 Connector: 9-pin D-auto  
 Signals: RS232 max  
 Total Connectors:.....  
 2xLNB Input; 2xSCART (TV/VCR);  
 3xJACKS RCA; 1xRS232  
 Power: 90-260V,50/60Hz  
 Consumption: 30w

### Dimensions

Size: 280x210x60mm  
 Weight: 1.6Kg