

Outdoor High Speed Dome Camera



Model: SH-561

Part #: D-Max DCS230Se

Features

- 1/4 " SONY Super HAD CCD
- 6.6-inch Bubble((Poly-Carbonate)Vandal proof)
- 360° Continuous, 92° Vertical
- Pan Speed:360°/sec, Tilt Speed:200°/sec
- Auto Flip(180°)
- Alarm : 4CH Active high/low selective input, 1 Relay output

Specifications

Signal system: PAL
 Image Sensor:
 1/4" Sony HAD CCD
 Number of Total Pixels:.....
 795(H) X 596(V), 470K
 Number of Effective Pixels:
 752(H) X 582(V), 440K
 Horizontal Resolution:.....
 More than 480 TV lines
 Lens: 22x Optical zoom, F 1.6(Wide), f =3.9 - 85.8mm
 Digital Zoom:
 10x (Total zoom 220x)
 Video Output:....
 1 Vp-p Composite video output 75 ohm terminated
 Brightness: Control Level (0 - 99)
 Shutter Speed Control:....
 1/60 - 1/10,000 sec 28 steps 1/50 - 1/10,000 sec 28 steps
 Flickerless Set: Off / On
 Sharpness Control Level: (0 - 15)
 Day&Night: On(0.1Lux) / Off
 DSS Control Max.: 32 Fields
 Auto Flip; On / Off
 Pan Angle: 360°Continuous
 Pan Speed:.....
 Manual: 0.1°~ 250°/sec (64 levels),
 Preset: Max 360°/sec (64 levels)
 Speed Control: Lower / Middle / High
 Tilt Angle: -2°~ 92°
 Preset Point: 128 Presets
 Alarm: 4 Input / 1 Relay Output
 Alarm Resume Control:
 Off, 1 ~ 180 sec
 Operating Temperature:.....
 - 40° to 60° (-40° to 140°)
 Storage Temperature: - 5° to 60°
 Operating Fan Ambient:.....
 Over than 50°
 Operating Humidity:
 less than 90%RH
 Power Consumption: 18W (Max)
 Power Supply: AC24V, 60/50 Hz

Dimensions

Size: 217D x 271H mm
 Weight About 4.3Kg
 (Without bracket)

- Applications:**
- Camera Security for Luxury Homes
 - CCTV Security at Luxury Offices
 - Hotel Security and Surveillance
 - Smart School Supervision and Observation