

Weatherproof Proximity Reader



Model: SH-573

Part #: Hundure PXR -50E

Features

- Compact and advanced design.
- Quick response, low interference, low power consumption and highly stable.
- Provide different kind of the reading range, up to 8cm (max).
- Interface: ABA T2, Wiegand 26 bit.
- Weather proof, suitable to use in all places.
- Provide LED & Buzzer control input and can fit all controllers.
- The Case sensor provide the controller to guard against remove when destroy by violence, the warming message will be show.

Specifications

Communication interface ... T2=ABA
 Track 2 W=Wiegand 485=RS-485
 485 Baud rate 19200bps-N-8-1
 Input device 1 (Case sensor)
 Frequency : 125Khz
 Indicators : 1 dual of color LED (Power / Status)
 Reading range: 6-8cm (max)
 Beep tone: Buzzer
 Operating voltage: DC 12V@200mA
 Power consumption: 1.5W (max)
 Temperature: -10degC – 55degC / 14F -131F
 Humidity: 20% - 95% (non-condensing)

Dimensions

Size: 44W x 95L x 16H(mm)
 Weight: 55g

- Applications:**
- Apartment buildings and Condominiums
 - Senior citizen buildings
 - Assisted care centers
 - Retirement homes
 - Gated communities