



Dimmer

Description:

ULTI Dimmer is an independent radio frequency controllable on/off and dimming switch.

Product Features:

RF Receiver

- Completely Retrofittable replaces any standard switch without rewiring
 - receives RF signals from ULTI Remote Control


Units

LED Backlight - turns on when switch is OFF for ease of


positioning


Service Switch - cuts off power source completely


Dimensions:



Front View (1 Gang Dimmer)







Front View (2 Gang Dimmer)

10July2003 (2)

Specifications:

PRODUCT SPECIFICATION	1-Gang 400W EMC Dimmer	2-Gang 2 x 200W EMC Dimmer	1-Gang 600W Dimmer	2-Gang 2 x 300W Dimmer		
Memory	8 Remote Control Units					
Load Type	Incandescent and Halogen Lamps					
Minimum Load	1 x 40W	2 x 40W	1 x 40W	2 x 40W		
Maximum Load Current	1 x 400W	5 x 500M	1 x 600W	2 x 300M		
Operating Temperature Range	0°C to + 40°C					
Operating Humidity Range	0% to 95%					
Operating Voltage	240V A.C.					
Operating Frequency	50Hz ± 1Hz					
Mounting Centers	60.3mm					
Dimensions	87mm(H) x 87mm(W) x 43mm(D)					
Power Cut Off	Service Switch					
Receiver Frequency	315MHz					

Ordering Information:

PRODUCT	Crystal Glass	Brushed Silver	Champagne Gold	Pearl White		
1-Gang 400W EMC Dimmer	U101DST400 BGL	U101DST400 BBS	U101DST400 ACG	U101DST400 BPW		
2-Gang 2 x 200W EMC Dimmer	U102DST400 BGL	U102DST400 BBS	U102DST400 ACG	U102DST400 BPW		
1-Gang 600W Dimmer	U101DSN600 BGL	U101DSN600 BBS	U101DSN600 ACG	U101DSN600 BPW		
2-Gang 2 x 300W Dimmer	U102DSN600 BGL	U102DSN600 BBS	U102DSN600 ACG	U102DSN600 BPW		



A II CLIPSAL CONCEPT