



simultaneous interpretation systems

Telecor's Simultaneous Interpretation System enables multiple translated languages to be transmitted to delegates throughout a conference facility. The system is available in 2 or 4 channels, each channel distributing a separate language.

The system can be used independently or combined with Telecor's Conference Systems, providing a total solution for any facility.

Delegates are provided with personal infrared receivers and headphones, and can select the language of his/her choice by means of a channel selector on the receiver. With the wireless receivers, the delegates have the freedom of unrestricted movement throughout the hall, and yet can receive the signal transmission from any location within the room. The number of delegates able to receive the signals from the infrared system is theoretically unlimited. A high level of security is ensured as infrared signals cannot pass through walls, remaining in the confines of the room.



telecor[™]

infraRed
Wireless

Telecor 4 channel Infrared system components

Receivers

The Receivers accommodate up to 4 language channels each. They are easy to use, lightweight, compact, and comfortable to wear. Users can choose the desired channel from a channel selector conveniently located on the top of the receiver. Volume levels can be adjusted to a comfortable listening level through the use of a volume control.

State-of-the-art electronics assure excellent speech intelligibility, high maximum volume, and low power consumption for long battery life. Models can be fitted with either disposable or rechargeable batteries. Each receiver employs dual IR detectors which provide superb sensitivity. This ensures reliable reception even at the fringe of the reception zone.



Headphones

Several headphone types are available for use with the receiver—from the conventional dynamic type to the ultra-lightweight stethoscope models. This offers optimum choice for any conference situation.

Emitter Panels

The Emitter Panels distribute the IR signals throughout a room or conference hall. They can be mounted on walls, ceilings, and floor stands. These high efficiency Panels allow a large floor area to be covered economically by a few units.



Modulators

The modulators generate a carrier wave for each of the 4 language channels and drive the Emitter Panels. The Modulators are compact in design, occupying a single rack space for all 4 channels.



- Language Interpretation
 - Conferences
- Multi-Media Rooms
 - Boardrooms
 - Courtrooms
 - Schools
 - Universities
- Government Facilities



telecorTM
www.telecor.com

In the USA: 165 Kirkland Circle, Oswego, Illinois 60543 Phone: (630) 236-8400 Fax: (630) 978-2201
In Canada: 1114 Westport Crescent, Mississauga, Ontario L5T 1G1 Phone: (905) 564-0801 Fax: (905) 564-0806
In the UK: Unit 3a, 21 Coopers Court, Coopers Yard, Newport Pagnell; Milton Keynes MK16 8JS; Buckinghamshire
Phone: 44-(0)-1908-211782 Fax: 44-(0)-1908-216946

Rev: 0.0
ETS- 2361
Printed in Canada

Telecor, the Telecor logo are Trademarks or Registered Trademarks of Telecor Inc.

